

Crystal Oscillator

YSO130HR High Voltage




Applications

- Consumer Electronics
- Industrial Control

Features

- Frequency range: 1MHz-100MHz.
- Ultra Small SMD seam sealed crystal oscillator units.
- Package Size: 3.2*2.5, 5.0*3.2 7.0*5.0mm



Specifications (规格参数)

Item	Symbol	Specifications
Frequency Range (额定频率范围)	f _o	1MHz to 100MHz, or specify
Supply Voltage (电源电压)	V _{cc}	5V
Output Type (输出方式)	-	CMOS
Frequency Tolerance (频率偏差) (at 25°C)	f _{tol}	±10ppm, ±20ppm, or specify
Output Load (输出负载)	L _{cmos}	15pF
Operating Temperature (工作温度)	T _{use}	-40~+85°C, or specify
Storage Temperature (储存温度)	T _{stg}	-55~+125°C
Frequency Versus Temperature Characteristics (频率-温度特性)	f _{tem}	± 20ppm, ± 30ppm, ± 50ppm, or specify
Duty Cycle (占空比)	SYM	45~55%
Start-up Time (启动时间)	t _{str}	3ms Max.
Rise Time/Fall Time (上升沿/下降沿)	tr/tf	4ns Max
Phase Jitter [12 kHz ~ 20 MHz] (相位抖动)	tpj	0.7ps max
Frequency Aging (老化) (at 25°C)	f _{age}	±3ppm/year Max.


Current Consumption (消耗电流)

Power Dissipation 15pF only		
Frequency	5V	
	7050/5032	3225
1~36MHZ	8mA max	8mA max
36~70MHZ	20mA max	20mA max
70~100MHZ	55mA max	25mA max

Pin Dimension (脚位尺寸)

Pin	#1	#2	#3	#4
FUNCTION	Tri-state	GND	OUTPUT	VDD

Pin Assignments



*The picture on the right is only for PIN function description.

Crystal Oscillator



YSO130HR High Voltage



Dimensions and Recommended land pattern (外观尺寸及推荐焊盘)

Package Size - Dimensions(Unit:mm)	Recommended Land Pattern(Unit:mm)
<p>3.2*2.5mm</p>	
<p>5.0*3.2mm</p>	
<p>7.0*5.0mm</p>	

Notes:

1.A capacitor value-0.01uf~0.1uf or higher between Vdd and GND is required.

Crystal Oscillator

YSO130HR High Voltage

Test Circuit (测试电路)

