

Crystal Unit

AEC-Q200

YSX530SC




Applications

- Automotive
- Industrial

Features

- Dimensions: 5.00 x 3.20 x 1.10mm
- Standard Frequency: 7.4 ~ 54MHz
- 2 pads SMD Metal Sealed Crystal Unit



Specifications (规格参数)

Item	Symbol	Specifications
Nominal Frequency Range 额定频率范围	f_nom	7.4 ~ 54MHz
Vibration Mode 震动模式	-	AT Fundamental
Load Capacitance 负载电容	CL	18pF, 20pF, or specify
Frequency Tolerance 频率偏差(at 25°C)	f_tol	±10ppm, ±20ppm, or specify
Frequency Versus Temperature Characteristics 频率-温度特性	f_tem	±50ppm, or specify
Operating Temperature 工作温度	T_use	-40~+125°C, or specify
Storage Temperature 储存温度	T_stg	-55~+125°C
Shunt Capacitance 静态电容	C0	5pF Max
Level of Drive 激励电平	DL	1~300μW Max(100μW typical)
Aging 老化(at 25°C)	f_age	±2ppm/year Max

Equivalent Series Resistance (等效串联电阻(ESR))

YSX530SC			
7.6 ~ 11.9MHz	100Ω Max	14 ~ 19.9MHz	50Ω Max
12 ~ 13.9MHz	60Ω Max	20 ~ 54MHz	40Ω Max

Dimensions and Recommended Land Pattern (外观尺寸及推荐焊盘)

Dimensions (Unit: mm)	Recommended Land Pattern (Unit: mm)
Top View Side View Bottom View	Top View Crystal Connection Top View Suggested Layout