

Crystal Oscillator AEC-Q200 YSO140TC




Applications

- Vehicle Assistance ,such as in-vehicle infotainment and smart cockpit.

Features

- Frequency range: 1MHz ~ 54MHz
- AEC-Q200

- Package Size: 1.6*1.2, 2.0*1.6, 2.5*2.0 , 3.2*2.5, 5.0*3.2, 7.0*5.0mm



Specifications (规格参数)

Item	Symbol	Specifications
Frequency Range 额定频率范围	f _o	1 ~ 54MHz, or specify
Supply Voltage 电源电压	VDD	1.8V ~ 3.3V
Output Type 输出方式	-	CMOS
Frequency Tolerance over Operating Temperature Range 频率频差	f _{tol}	±50ppm, ±100ppm, or specify
Output Load 输出负载	L _{cmos}	15pF
Operating Temperature 工作温度	T _{use}	-40 ~+ 125°C, or specify
Storage Temperature 储存温度	T _{stg}	-55 ~+ 150°C
Output Voltage 输出电压	V _{oh}	90%VDD Min
	V _{ol}	10%VDD Max
Duty Cycle 占空比	SYM	45 ~ 55%
Start-up Time 启动时间	t _{str}	3ms Max
Rise Time/Fall Time 上升沿/下降沿	tr/tf	5ns Max
Phase Jitter [12 kHz ~ 20 MHz] 相位抖动	tpj	0.7ps Max
Frequency Aging 老化(at 25°C)	f _{age}	±3ppm/year Max
Tri-State	Enable (High Voltage or Floating)	70% of VDD Min
	Disable (Low Voltage or GND)	30% of VDD Max

Current Consumption (消耗电流)

Power Dissipation Vcc=1.8~3.3V 15pF only				
Supply Voltage	1.000~40.000MHZ		41.000~54.000MHZ	
	7050/5032/3225	2520/2016/1612	7050/5032/3225/2520	2016/1612
1.8V	4mA Max	4mA Max	9mA Max	10mA Max
2.5V	4.5mA Max		10mA Max	
3.3V	5mA Max		12mA Max	

Please contact us for current consumption for frequencies above 54MHz.

Crystal Oscillator AEC-Q200 YSO140TC




Pin Dimension (脚位尺寸)

Pin	#1	#2	#3	#4
FUNCTION	Tri-state	GND	Output	VDD

*The picture on the right is only for PIN function description.

Pin Assignments



Dimensions and Recommended land pattern (外观尺寸及推荐焊盘)

Package Size – Dimensions (Unit: mm)	Recommended Land Pattern (Unit: mm)
1.6*1.2mm Top View Side View Bottom View	Recommended soldering Pattern
2.0*1.6mm Top View Side View Bottom View	Recommended soldering Pattern
2.5*2.0mm Top View Side View Bottom View	Recommended soldering Pattern

Crystal Oscillator AEC-Q200 YSO140TC



3.2*2.5mm Top View Bottom View Side View	Recommended soldering Pattern
5.0*3.2mm Top View Bottom View Side View	Recommended soldering Pattern
7.0*5.0mm Top View Bottom View Side View	Recommended soldering Pattern
Notes: 1.A capacitor of value 0.01uf~0.1uf or higher between Vdd and GND is required.	

Crystal Oscillator AEC-Q200 YSO140TC



Test Circuit (测试电路)

